

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

Identity (As Used on Label and List)

PROPANE

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

SECTION 1	
Supplier's Name Bernz-O-matic	Emergency Telephone Number 585-798-4949
Address <i>Number, Street, City, State and ZIP Code</i> One BernzOmatic Drive Medina, NY 14103	Telephone Number for Information 585-798-4949
	Date Prepared January 01, 2003
	Signature of Preparer (Optional)

SECTION 2				
Hazardous Components <i>Specific Chemical Identity, Common Name(s)</i> PROPANE CAS #74-98-6	OSHA PEL 1000PPM	ACGIH TLV 1000PPM	Other Limits Recommended NA	% (optional) 100
NFPA HAZARD RATINGS Health -1 Flammability -4 Reactivity -0	HMIS RATINGS Health -0 Flammability -4 Reactivity -0			

Note: When propane fuel is burned efficiently, the normal by-products of combustion are CO₂ and H₂O. Inefficient burning may add CO to the by-products of combustion.

SECTION 3			
Boiling Point -44° F	Specific Gravity (H ₂ O = 1) Liquid @ 60° F .51		
Vapor Pressure (mm Hg) @ 100° F 197 psig	Melting Point N/A		
Vapor Density (AIR=1) @ 1 ATM @ 60° F 1.56	Evaporation Rate Butyl Acetate (-1) N/A		
Solubility in Water Not Soluble			

Appearance and Odor
Colorless - Rotten Egg Odor

SECTION 4			
Flash Point (Method Used) -156° F Closed Cup	Flammable Limits	LEL 2.1	UEL 9.5

Extinguishing Media
Stop flow of gas or oxygen

Special Fire Fighting Procedures
Use water to cool tanks

Unusual Fire and Explosion Hazards
**Auto Ignition temp. 842° F Heavier than air (vapor density 1.5).
May travel a considerable distance to a source of ignition and flashback.**

SECTION 5	
Stability → Unstable Stable X	Conditions to Avoid N/A
Incompatibility (Materials to Avoid) N/A	
Hazardous Decomposition or Byproducts None	
Hazardous Polymerization → May Occur Will Not Occur X	Conditions to Avoid N/A

Routes of Entry →	Inhalation? YES	Skin? YES	Ingestion? NO
--------------------------	----------------------------	----------------------	--------------------------

Health Hazards (Acute and Chronic)
Contact with liquid propane may cause frost burns

Carcinogenicity →	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A
--------------------------	---------------------	---------------------------------	--------------------------------

Signs and Symptoms of Exposure
High concentrations may cause headaches and drowsiness.

Medical Conditions Generally Aggravated by Exposure
N/A

Emergency and First Aid Procedures
Remove exposed person from contaminated area.

Warning
This fuel, and byproducts of combustion of this fuel, contain chemicals known to the State of California to cause cancer, birth defects, and other reproductive harm.

Steps to be Taken in Case Material is Released or Spilled
Remove ignition sources and ventilate area.

Waste Disposal Method
Vent gas to atmosphere in flame free, spark free area outdoors.

Precautions to be Taken in Handling and Storing
Store at temperatures below 120° F in well ventilated, spark free, flame free area.

Other Precautions
None

Respiratory Protection (Specify Type)
Not required with normal use.

Ventilation →	Local Exhaust N/A	Mechanical (General) N/A	Special N/A	Other N/A
----------------------	------------------------------	-------------------------------------	------------------------	----------------------

Protective Gloves Not required	Eye Protection Not required
---	--

Other Protective Clothing or Equipment
Not required

Work / Hygienic Practices
N/A

WHMIS Classification: A - Compressed Gas & B1-Flammable Gas		Class: 2.1	
DOT	Proper Shipping Name Petroleum Gas, Liquefied	Hazard Classification Flammable Gas	UN. No. 1075