

267468 Part# MP5317-5  
 BLOCK FILLER, 5-GAL. #5317  
 60 ICI PAINTS  
 Buyer: Bernard W. Aubuchon Jr.

# MATERIAL SAFETY DATA SHEET

Glidden

## HAZARDS IDENTIFICATION (ANSI Section 3)

**Primary route(s) of exposure :** Inhalation, skin contact, eye contact, ingestion.  
**Effects of overexposure :**  
**Inhalation :** Irritation of respiratory tract. Prolonged inhalation may lead to mucous membrane irritation, chest pain, coughing, difficulty of breathing, severe lung irritation or damage, pneumoconiosis.  
**Skin contact :** Irritation of skin.  
**Eye contact :** Irritation of eyes. Prolonged or repeated contact can cause tearing of eyes, redness of eyes.  
**Ingestion :** Ingestion may cause mouth and throat irritation, nausea, gastro-intestinal disturbances, abdominal pain.  
**Medical conditions aggravated by exposure :** Eye, skin, respiratory disorders asthma-like conditions respiratory disorders

## FIRST-AID MEASURES (ANSI Section 4)

**Inhalation :** Remove to fresh air. Restore and support continued breathing. Get emergency medical attention. Have trained person give oxygen if necessary. Get medical help for any breathing difficulty. Remove to fresh air if inhalation causes eye watering, headaches, dizziness, or other discomfort.  
**Skin contact :** Wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin. Repeated applications may be needed. Remove contaminated clothing. Wash contaminated clothing before re-use.  
**Eye contact :** Flush immediately with large amounts of water, especially under lids for at least 15 minutes. If irritation or other effects persist, obtain medical treatment.  
**Ingestion :** If swallowed, obtain medical treatment immediately.

## FIRE-FIGHTING MEASURES (ANSI Section 5)

**Fire extinguishing media :** Dry chemical or foam water fog. Carbon dioxide. Closed containers may burst if exposed to extreme heat or fire. In closed tanks, water or foam may cause frothing or eruption.  
**Fire fighting procedures :** Water may be used to cool and protect exposed containers. Firefighters should use full protective clothing, eye protection, and self-contained breathing apparatus.  
**Hazardous decomposition or combustion products :** Carbon monoxide, carbon dioxide, Sodium oxide, Oxides of calcium

## ACCIDENTAL RELEASE MEASURES (ANSI Section 6)

**Steps to be taken in case material is released or spilled :** Comply with all applicable health and environmental regulations. Eliminate all sources of ignition. Ventilate area. Evacuate all unnecessary personnel. Place collected material in proper container. Small spills - use absorbent to pick up residue and dispose of properly.

## HANDLING AND STORAGE (ANSI Section 7)

**Handling and storage :** Store below 100°F (38°C). Keep from freezing.  
**Other precautions :** Use only with adequate ventilation. Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes, and breathing of vapors. Wash hands thoroughly after handling, especially before eating or smoking. Keep containers tightly closed and upright when not in use. Avoid conditions which result in formation of inhalable particles such as spraying or abrading (sanding) painted surfaces. If such conditions cannot be avoided, use appropriate respiratory protection as directed under exposure controls/personal protection.

## EXPOSURE CONTROLS/PERSONAL PROTECTION (ANSI Section 8)

**Respiratory protection :** Control environmental concentrations below applicable exposure standards when using this material. When respiratory protection is determined to be necessary, use a NIOSH/MSHA (Canadian 294.4) Approved elastomeric sealing- surface facepiece respirator outfitted with organic vapor cartridges and paint spray (dust/mist) prefilters. Determine the proper level of protection by conducting appropriate air monitoring. Consult 29CFR1910.134 For selection of respirators (Canadian 294.4).  
**Ventilation :** Provide dilution ventilation or local exhaust to prevent build-up of vapors.  
**Personal protective equipment :** Eye wash, safety shower, safety glasses or goggles. Impervious gloves, impervious clothing.

## STABILITY AND REACTIVITY (ANSI Section 10)

**Under normal conditions :** Stable see section 5 fire fighting measures  
**Materials to avoid :** Oxidizers, acids, bases.  
**Conditions to avoid :** Elevated temperatures, contact with oxidizing agent, freezing, sparks, open flame.  
**Hazardous polymerization :** Will not occur

## TOXICOLOGICAL INFORMATION (ANSI Section 11)

**Supplemental health information :** No additional effects are anticipated  
**Carcinogenicity :** Inhalation of non-asbestiform cosmetic grade talc for 2 years at 6 and 18 mg/m<sup>3</sup> produced clear evidence of carcinogenicity in female rats (lung and adrenal tumors) and some evidence of carcinogenicity in male rats (adrenal tumors). No evidence of carcinogenicity was demonstrated in male and female mice exposed under the same conditions. Microscopic examination of the lungs of rats and mice exposed to talc revealed additional exposure related effects primarily associated with the inflammatory response. Contains crystalline silica which is considered a hazard by inhalation. IARC has classified crystalline silica as carcinogenic to humans (group 1). Crystalline silica is also a known cause of silicosis, a noncancerous lung disease. The national toxicology program (NTP) has classified crystalline silica as a known human carcinogen.

**Reproductive effects :** No reproductive effects are anticipated  
**Mutagenicity :** No mutagenic effects are anticipated  
**Teratogenicity :** No teratogenic effects are anticipated

## ECOLOGICAL INFORMATION (ANSI Section 12)

No ecological testing has been done by ICI paints on this product as a whole.

## DISPOSAL CONSIDERATIONS (ANSI Section 13)

**Waste disposal :** Dispose in accordance with all applicable regulations. Avoid discharge to natural waters.

## REGULATORY INFORMATION (ANSI Section 15)

As of the date of this MSDS, all of the components in this product are listed (or are otherwise exempt from listing) on the TSCA inventory. This product has been classified in accordance with the hazard criteria of the CPR (controlled products regulations) and the MSDS contains all the information required by the CPR.

The information contained herein is based on data available at the time of preparation of this data sheet which ICI Paints believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. ICI Paints shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and the users of this material. Complies with OSHA hazard communication standard 29CFR1910.1200.

**Physical Data**

(ANSI Sections 1, 9, and 14)

Product Code	Description	Wt. / Gal.	VOC gr. / ltr.	% Volatile by Volume	Flash Point	Boiling Range	HMIS	DOT, proper shipping name
MP 5300	promaster architectural latex flat white	11.57	88.68	67.95	none	100-105	110	paint ** protect from freezing **
MP 5302	promaster architectural latex flat antique white	11.52	88.08	68.63	none	212-212	110	paint
MP 5310	promaster architectural latex flat white tint base	11.57	88.68	67.95	none	100-105	*110	paint ** protect from freezing **
MP 5318	promaster architectural latex flat pastel tint base	11.65	96.59	67.31	none	100-105	*110	paint ** protect from freezing **
MP 5380	promaster architectural latex flat deep tint base	10.16	83.64	71.84	none	100-105	110	paint ** protect from freezing **
MP 5387	promaster architectural latex flat intermediate tint base	10.69	77.17	68.62	none	100-105	110	paint ** protect from freezing **

**Ingredients**

Product Codes with % by Weight (ANSI Section 2)

Chemical Name	Common Name	CAS. No.	MP 5300	MP 5302	MP 5310	MP 5318	MP 5380	MP 5387
limestone	limestone	1317-65-3				10-20		
silicic acid, aluminum sodium salt	sodium aluminosilicate	1344-00-9	1-5	1-5	1-5			
titanium oxide	titanium dioxide	13463-67-7	5-10	10-20	5-10	1-5		1-5
talc	talc	14807-96-6	10-20		10-20	5-10		
quartz	quartz	14808-60-7	1-1.0		1-1.0			
2-propenoic acid, butyl ester, polymer with ethenyl acetate	vinyl acrylic latex	25067-01-0	5-10	5-10	5-10	5-10	10-20	10-20
propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol	texanol	25265-77-4	1-5	1-5	1-5	1-5	1-5	1-5
nepheline syenite	feldspar-type minerals	37244-96-5		10-20			10-20	10-20
ceramic materials and waxes, chemicals	calcined kaolin clay	66402-68-4	10-20	5-10	10-20	10-20	5-10	10-20
water	water	7732-18-5	40-50	40-50	40-50	40-50	50-60	50-60

**Chemical Hazard Data**

(ANSI Sections 2, 8, 11, and 15)

Common Name	CAS. No.	ACGIH-TLV			OSHA-PEL					S.R. Std.	H	M	N	I	O
		8-Hour TWA	STEL	C	S	8-Hour TWA	STEL	C	S						
limestone	1317-65-3	10 mg/m3	not est.	not est.	not est.	5 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n
sodium aluminosilicate	1344-00-9	10 mg/m3	not est.	not est.	not est.	5 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n
titanium dioxide	13463-67-7	10 mg/m3	not est.	not est.	not est.	10 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n
talc	14807-96-6	2 mg/m3	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n
quartz	14808-60-7	0.5 mg/m3	not est.	not est.	not est.	0.1 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n
vinyl acrylic latex	25067-01-0	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n
texanol	25265-77-4	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n
feldspar-type minerals	37244-96-5	5 mg/m3	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n
calcined kaolin clay	66402-68-4	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n

Footnotes:  
 C=Ceiling - Concentration that should not be exceeded, even instantaneously.  
 S=Skin - Additional exposure, over and above airborne exposure, may result from skin absorption.  
 n/a=not applicable  
 not est.=not established  
 CC=CERCLA Chemical  
 ppm=parts per million  
 mg/m3=milligrams per cubic meter  
 Sup Conf=Supplier Confidential  
 S2=Sara Section 302 EHS  
 S3=Sara Section 313 Chemical  
 S.R.Std.=Supplier Recommended Standard  
 H=Hazardous Air Pollutant, M=Marine Pollutant  
 P=Pollutant, S=Severe Pollutant  
 Carcinogenicity Listed By:  
 N=NTP, I=IARC, O=OSHA, y=yes, n=no