



**Gillette Medical  
Evaluation  
Laboratories**

605118 Part# 8247421  
MN1500B2Z BATTERY AA  
445 ORGILL INC. (BUXTON ONLY)  
Buyer: Bernard W. Aubuchon Jr.

37 A Street  
Needham, MA 02492  
781.292.8151

## MATERIAL SAFETY DATA SHEET

**NAME:** DURACELL ALKALINE BATTERIES

**CAS NO:** Not applicable

**Effective Date:** 05/30/2001 **Rev:** 5

### A. — IDENTIFICATION

<u>Composition*</u> (1% or greater)	%	Formula: Mixture
Manganese Dioxide (1313-13-9)	35-40	Molecular Weight: NA
Zinc (7440-66-6)	10-15	Synonyms: Alkaline Manganese Dioxide Batteries MN1300 (D); MN1400 (C); MN1500 (AA) MN2400 (AAA); MN908 (Lantern 6V); MN918 (Lantern 4.5V); MN1604 (9V); MN9100 (N), DAC100, 105,110,116- 118,123-124, 130, 200, 610,810,820,918, 5K69 (Flatpack); 7K67 (Flatpack) (J) and batteries comprised of these cells.
Potassium Hydroxide (35%) (1310-58-3)	5-10	
Carbon Black (1333-86-4) or Graphite, natural (7782-42-5) or synthetic (7440-44-0)	1-5	
Zinc Oxide (1314-13-2)	0-1	

### B. — PHYSICAL DATA

Boiling Point NA °F NA °C	Melting Point NA °F NA °C	Freezing Point NA °F NA °C
Specific Gravity (H <sub>2</sub> O=1) NA	Vapor Density (air=1) NA	Vapor Pressure @ _____ °F NA mm Hg
Evaporation (Ether =1) NA	Saturation in Air (by volume @ _____ °F) NA	Autoignition Temperature °F °C NA
% Volatiles NA	Solubility in Water NA	pH NA

**Appearance/Color** Copper top battery. Contents dark in color.

**Flash Point and Test Method(s)** NA

**Flammable Limits in Air**  
(% by volume) Lower NA % Upper NA %

### C. — REACTIVITY

Stability	<input checked="" type="checkbox"/> Stable	<input type="checkbox"/> Unstable	Polymerization	<input type="checkbox"/> may occur	<input checked="" type="checkbox"/> will not occur
<u>Conditions to Avoid</u>			<u>Conditions to Avoid</u>		
Do not heat, crush, disassemble, short circuit or recharge.			Not applicable		
<u>Incompatible Materials</u>			<u>Hazardous Decomposition Products</u>		
Contents incompatible with strong oxidizing agents.			Thermal degradation may produce hazardous fumes of zinc and manganese; hydrogen gas; caustic vapors of potassium hydroxide and other toxic by-products.		

**Footnotes**

NA=Not Available

Please note: Some Duracell alkaline batteries contain the Duracell Power Check™ battery energy gauge which is a small conductive strip located underneath the PVC battery label that indicates the amount of charge in the battery. It is composed of minute quantities of conductive materials. Due to the small quantity of materials and their solid form, a health or environmental risk is unlikely.

**D. — HEALTH HAZARD DATA**

Occupational Exposure Limits (PELs, TLVs, etc.)

8-Hour TWAs: Manganese Dioxide (as Mn) - 5 mg/m<sup>3</sup> (Ceiling) (OSHA); 0.2 mg/m<sup>3</sup> (ACGIH/Duracell)  
 Potassium Hydroxide - 2 mg/m<sup>3</sup> (Ceiling) (ACGIH)  
 Graphite (all kinds except fibrous)-2 mg/ m<sup>3</sup> (ACGIH); (synthetic)-15 mg/m<sup>3</sup> (total, OSHA );  
 5 mg/m<sup>3</sup> (respirable, OSHA)  
 Carbon Black - 3.5 mg/m<sup>3</sup> (ACGIH/OSHA)  
 Zinc Oxide (dust) - 10 mg/m<sup>3</sup> (ACGIH), 15 mg/m<sup>3</sup> (total, OSHA);  
 5 mg/m<sup>3</sup> (respirable, OSHA)

These levels are not anticipated under normal consumer use conditions.

Warning Signals

Not applicable

Routes/Effects of Exposure

These chemicals and metals are contained in a sealed can. For consumer use, adequate hazard warnings are included on both the package and on the battery. Potential for exposure should not exist unless the battery leaks, is exposed to high temperatures or is mechanically, physically, or electrically abused. Contains concentrated (35%) potassium hydroxide, which is caustic. Anticipated potential leakage of potassium hydroxide is 2 to 20 ml, depending on battery size. A similar amount of zinc/zinc oxide may also leak.

- |                |   |
|----------------|---|
| 1. Inhalation  | Respiratory (and eye) irritation may occur if fumes are released due to heat or an abundance of leaking batteries.  |
| 2. Ingestion   | Not anticipated due to size of batteries; choking may occur with the smaller AAA and AAAA batteries. Irritation, including caustic burns/injury, may occur following exposure to a leaking battery. |
| 3. Skin        | <p>a. <u>Contact</u><br/>Irritation, including caustic burns/injury, may occur following exposure to a leaking battery.</p> <p>b. <u>Absorption</u><br/>Not anticipated</p>                         |
| 4. Eye Contact | Irritation, including caustic burns/injury, may occur following exposure to a leaking battery.  |
| 5. Other       | Not applicable  |

**E. — ENVIRONMENTAL IMPACT**

- |                             |   |
|-----------------------------|---|
| 1. Applicable Regulations - | All ingredients listed in TSCA inventory.   |
| 2. DOT Hazard Class -       | Not applicable  |
| 3. DOT Shipping Name -      | <p>Not applicable</p> <p>Please note: These batteries are not regulated by U. S. DOT or international agencies as hazardous materials or dangerous goods when shipped. Duracell uses the article name 'Alkaline Batteries - Non-hazardous' on all domestic and international bills of lading.</p> |

Environmental Effects

These batteries pass the U. S. EPA's Toxicity Characteristic Leaching Procedure and therefore, may be disposed of with normal waste.

**F. — EXPOSURE CONTROL METHODS**

## Engineering Controls

General ventilation under normal use conditions.

## Eye Protection

None under normal use conditions. Wear safety glasses when handling leaking batteries.

## Skin Protection

None under normal use conditions. Use neoprene, rubber or latex gloves when handling leaking batteries.

## Respiratory Protection

None under normal use conditions.

## Other

Keep batteries away from small children.

**G. — WORK PRACTICES**

## Handling and Storage

Store at room temperature. Avoid mechanical or electrical abuse. **DO NOT** short or install incorrectly. Batteries may explode, pyrolyze or vent if disassembled, crushed, recharged or exposed to high temperatures. Install batteries in accordance with equipment instructions. Do not mix battery systems, such as alkaline and zinc carbon, in the same equipment. Replace all batteries in equipment at the same time. Do not carry batteries loose in pocket or bag. Do not remove battery tester or battery label.

## Normal Clean Up

Not applicable

## Waste Disposal Methods

Individual consumers may dispose of spent (used) batteries with household trash. Duracell does not recommend that spent batteries be accumulated (quantities of five gallons or more should be disposed of in a secure landfill), in accordance with appropriate federal, state and local regulations. Do not incinerate, since batteries may explode at excessive temperatures.

**H. — EMERGENCY PROCEDURES**

Steps to be taken if material is released to the environment or spilled in the work area  
 Notify safety personnel of large spills. Caustic potassium hydroxide may be released from leaking or ruptured batteries. Avoid eye or skin contact and inhalation of vapors. Increase ventilation. Clean-up personnel should wear appropriate protective gear.

**Fire and Explosion Hazard**

Batteries may burst and release hazardous decomposition products when exposed to a fire situation. See Sec. C.

**Extinguishing Media**

As appropriate for surrounding area.

**Firefighting Procedures**

Use self-contained breathing apparatus and full protective gear.

**I. — FIRST AID AND MEDICAL EMERGENCY PROCEDURES****Eyes**

Not anticipated. If battery is leaking and material contacts eyes, flush with copious amounts of clear, tepid water for 30 minutes. Contact physician at once.

**Skin**

Not anticipated. If battery is leaking, irrigate exposed skin with copious amounts of clear, tepid water for at least 15 minutes. If irritation, injury or pain persists, consult a physician.

**Inhalation**

Not anticipated. If battery is leaking, contents may be irritating to respiratory passages. Remove to fresh air. Contact physician if irritation persists.

**Ingestion**

Not anticipated. Rinse the mouth and surrounding area with clear, tepid water for at least 15 minutes. Consult a physician immediately for treatment and to rule out involvement of the esophagus and other tissues.

**Notes to Physician**

- 1) The primary acutely toxic ingredient is concentrated (35%) potassium hydroxide.
- 2) Anticipated potential leakage of potassium hydroxide is 2-20 ml, depending on battery size.
- 3) This MSDS does not include or address the small button cell batteries, which can be ingested.

Replaces #1898, #1360, consolidation of information for similar products.

The information contained in the Material Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.