

MSDS - Material Safety Data Sheet

Product Name: Plumbers Putty


MSDS No.: 043050

642528 Part# 6420152
 5LBS STAINLESS PLUMBERS PUTTY
 445 ORGILL INC. (WEB / STORE)
 Buyer: Kristine Albrecht

Part Numbers Covered:							
043000	043011	043022	043035	043049	043099	043111	043125
043001	043012	043023	043036	043050	043100	043112	043126
043002	043013	043024	043037	043051	043101	043113	043127
043003	043014	043025-D	043038	043052	043102	043114	043135
043004	043014-SP	043026	043039	043053	043103	043115	043137-D
043005	043015	043027	043040	043054	043104	043117	043145
043006	043016	043028	043041	043055	043105	043118	043150
043007	043016-D	043029	043042	043057	043105-D	043119	043155
043008	043017	043030	043043	043058	043106	043120	043175
043009	043018	043031	043045	043060	043107	043121	043255
043010	043019	043032	043046	043070	043108	043122	043265
043010-D	043020	043033	043047	043090	043109	043123	
043010-SP	043021	043034	043048	043095	043110	043124	

I. Basic Information:


Manufacturer: WILLIAM H. HARVEY COMPANY
Address: 4334 SOUTH 67TH STREET
City, ST Zip: OMAHA, NE 68117-1019



Last Update: 7/8/2002

Chemical State: Liquid Gas Solid

Chemical Type: Pure Mixture



II. Ingredients:

CAS No.	Chemical Name	% Range	EHS	NTP	IARC	SUB Z	SARA 313	OSHA PEL	ACGIH TLV	Other Limits
0	THIS ITEM IS NOT CLASSIFIED AS HAZARDOUS IN ACCORDANCE WITH OSHA 1910.1200.	NI						NI	NI	NI

III. Hazardous Identification:

Hazard Category: Acute Chronic Fire Pressure Reactive

Hazardous Identification Information:
 NDA

IV. First Aid Measures:

Route(s) of Entry:
 NI

Health Hazards (Acute and Chronic):
 NI

MSDS - Material Safety Data Sheet

Product Name: *Plumbers Putty*

MSDS No.: 043050

Signs and Symptoms:

EYES: MAY CAUSE EYE IRRITATION.

INHALATION: POSSIBLE LIGHT HEADEDNESS OR MAY CAUSE HEADACHE. INGESTION: HAS LAXATIVE PROPERTIES AND MAY RESULT IN ABDOMINAL CRAMPS AND DIARRHEA.

Medical Conditions Generally Aggravated by Exposure:

NI

Emergency and First Aid Procedures:

EMERGENCY FIRST AID CALL: 1-303-623-5716 COLLECT

REMOVE VICTIM TO FRESH AIR, SEEK MEDICAL ATTENTION IF CONDITION PERSISTS.

Other Health Warnings:

NI

V. Fire Fighting Measures:

Flash Point: 650 F DEG

Lower Explosive Limit: NI

Upper Explosive Limit:

Fire Extinguishing Media: CO2, FOAM AND DRY CHEMICAL

Special Fire Fighting Procedures:

USE WATER SPRAY TO COOL FIRE EXPOSED TO MATERIAL AND TO PROTECT PERSONNEL.

Unusual Fire and Explosion:

NI

VI. Accidental Release Measures:

Steps to be Taken in Case Material is Released or Spilled:

NO SPECIAL PRECAUTIONS - SCOOP UP SPILLED MATERIAL, IT CAN BE REUSED IF IT IS NOT DIRTY OR CONTAMINATED.

VII. Handling and Storage:

Precautions to be Taken:

STORE AWAY FROM HEAT, KEEP CONTAINER CLOSED AFTER USE.

Other Precautions:

KEEP OUT OF REACH OF CHILDREN AND PETS

VIII. Exposure Controls/Personal Protection:

Ventilation Requirements:

OPEN AREA IS SUFFICIENT

Personal Protective Equipment:

NO PROTECTIVE CLOTHING OR EQUIPMENT IS REQUIRED. USE NORMAL GOOD HYGIENIC PRACTICES.

MSDS - Material Safety Data Sheet

Product Name: Plumbers Putty

MSDS No.: 043050

XVI. Other Information:

ABBREVIATIONS:

N/A = NOT APPLICABLE N/I = NONE INDICATED NDA = NO DATA AVAILABLE
N/E = NOT ESTABLISHED C = CELSIUS DEGREES F = FAHRENHEIT DEGREES

DISCLAIMER:

THE INFORMATION HEREIN HAS BEEN COMPILED FROM SOURCES BELIEVED TO BE RELIABLE, UP-TO-DATE, AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, WILLIAM H. HARVEY COMPANY CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE WARRANTIES, NOR ASSUMES ANY LIABILITY FOR ITS USES.